

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
7 July 2005 (07.07.2005)

PCT

(10) International Publication Number
WO 2005/062395 A1

(51) International Patent Classification⁷: **H01L 41/053**

(21) International Application Number:
PCT/BP2004/052978

(22) International Filing Date:
16 November 2004 (16.11.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
03029640.4 22 December 2003 (22.12.2003) EP

(71) Applicant (for all designated States except US):
SIEMENS VDO AUTOMOTIVE SPA [IT/IT]; S.S.
206 - km 28 Loc. Luciana, I-56040 Fauglia/Pisa (IT).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **D'ARRIGO, Angelo**
[IT/IT]; Via Filangeri 28, I-57013 Rosignano Solvay (IT).

(74) Common Representative: **SIEMENS VDO AUTOMOTIVE SPA**; Peter Berg, European Patent Attorney, Postfach 22 16 34, I-80506 München (IT).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AH, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: **ACTUATOR UNIT AND METHOD FOR MANUFACTURING AN ACTUATOR UNIT**



(57) **Abstract:** An actuator unit comprises a tube spring (32), a piezoelectric actuator (31), that is inserted into the tube spring (32), a first cap (33), that is connected to the tube spring (32) at a first free end of the tube spring (32) and which is adjoined by the piezoelectric actuator (31), a tube-shaped body 38, that is connected to the tube spring (32) by joining and is arranged in the area of a second free end (35) of the tube spring (32), and a means for pretensioning, that is supported by the tube-shaped body (38) and pretensions the piezoelectric actuator (31). The actuator unit is simple and cheap to manufacture.

WO 2005/062395 A1